

OCPI v2.2.1 Protocol

IOP – OCPI Interface - Implementation Guide V1.2

Gireve

28/11/2024

1	INTRODUCTION	5
1.1	AIMS.....	5
1.2	INTENDED AUDIENCE.....	5
1.3	DEFINITIONS AND ABBREVIATIONS.....	5
1.4	CARDINALITY EXPRESSION.....	5
2	INTEGRATION GUIDELINES	7
2.1	TECHNICAL	7
2.1.1	<i>Supported OCPI versions</i>	7
2.1.2	<i>Security</i>	7
2.1.3	<i>Platform and operator identification</i>	8
2.1.4	<i>Traceability: X-Correlation-ID and X-Request-ID</i>	8
2.1.5	<i>Multi-tenant and multi-role capability</i>	9
2.1.6	<i>IOP is a "HUB"</i>	9
2.1.7	<i>Client owned object push</i>	9
2.1.8	<i>Pagination</i>	10
2.1.9	<i>Pulling Limits</i>	10
2.1.10	<i>List of OCPI modules</i>	10
2.1.11	<i>Gireve management of Ids</i>	11
2.2	GIREVE MANAGEMENT OF LOCATIONS DATA.....	11
2.3	ROAMING.....	12
2.3.1	<i>General workflow</i>	12
2.3.2	<i>Management of B2B tariffs</i>	13
2.3.3	<i>RFID Tokens</i>	14
3	CPO SPECIFIC IMPLEMENTATION GUIDELINES.....	15
3.1	GENERAL INFORMATION.....	15
3.1.1	<i>CPO operation definition and naming rules</i>	15
3.1.2	<i>CPO operation and roaming offers</i>	15
3.2	USE CASES COVERED BY IOP	16
3.3	USE CASES REQUIRED BY GIREVE.....	18
3.4	CONNECTION & REGISTER SPECIFICATIONS.....	19
3.5	LOCATIONS MODULE SPECIFICATIONS.....	19
3.5.1	<i>Locations information required by Gireve</i>	19
3.5.2	<i>Static and dynamic attributes</i>	20
3.5.3	<i>"tariff_ids" property</i>	20
3.5.4	<i>"publish" property</i>	21
3.5.5	<i>Plug&Charge (P&C)</i>	21
3.5.6	<i>Store and Forward – PUT and PATCH Locations</i>	21
3.6	TOKENS MODULE SPECIFICATIONS.....	22
3.6.1	<i>Download of Tokens not recommended</i>	22
3.6.2	<i>"LocationReferences" mandatory in POST Tokens Authorize requests</i>	22
3.7	COMMANDS MODULE SPECIFICATIONS	23
3.7.1	<i>List of available Commands</i>	23
3.7.2	<i>New field "connector_id" in START_SESSION</i>	23
3.8	SESSIONS MODULE SPECIFICATIONS.....	23
3.8.1	<i>Session initialisation</i>	23
3.8.2	<i>Smart charging use cases</i>	24
3.8.3	<i>PATCH Sessions</i>	24
3.8.4	<i>Store and forward – PUT Sessions</i>	24
3.8.5	<i>Advenir specific use case</i>	24
3.9	CDRs MODULE SPECIFICATIONS	25
3.9.1	<i>CDR sending frequency</i>	25
3.9.2	<i>CDR content</i>	25
3.9.3	<i>CreditCDR</i>	25

3.9.4	Store and forward – POST CDRs	26
3.9.5	Advenir specific use case	26
3.10	TARIFFS MODULE SPECIFICATION	27
3.10.1	Locations tariff update	27
3.10.2	Tariff shall be immutable	27
3.10.3	Tariff information required by Gireve	27
3.10.4	Differentiate tariff per eMSP	28
3.10.5	Tariffs are attached to the EVSE level	29
3.10.6	Store and forward – PUT Tariffs	29
4	EMSP SPECIFIC IMPLEMENTATION GUIDELINES	31
4.1	USE CASES COVERED BY IOP	31
4.1.1	Use cases required by Gireve	34
4.2	CONNECTION & REGISTER SPECIFICATIONS	34
4.3	LOCATIONS MODULE SPECIFICATIONS	35
4.3.1	Static and dynamic attributes	35
4.3.2	PULL Locations: Retrieve Locations of a single given CPO	35
4.3.3	PULL Locations ToIOP: Get List, Full and Delta modes	35
4.3.4	PULL Locations ToIOP: evse_id	36
4.3.5	PULL Locations ToIOP: “gireve_id” An Extra Gireve Property	36
4.3.6	PULL Locations ToIOP: tariff_ids	36
4.3.7	PULL Locations ToIOP: Plug&Charge (P&C)	36
4.3.8	PULL Locations ToIOP: Connector Standards	37
4.3.9	Fields Not Implemented by Gireve	37
4.3.10	PUSH Locations FromIOP	37
4.4	TOKENS MODULE SPECIFICATIONS	38
4.4.1	Push Tokens ToIOP	38
4.4.2	PULL Tokens FromIOP	38
4.5	COMMANDS MODULE SPECIFICATIONS	38
4.5.1	“ocpi-to-country-code” and “ocpi-to-party-id” headers mandatory in StartSession and StopSession commands	38
4.5.2	“evse_uid” mandatory in StartSession command	39
4.5.3	“connector_id” optional in StartSession command	39
4.5.4	ReserveNow command	39
4.5.5	CancelReservation command	39
4.5.6	UnlockConnector command	39
4.6	SESSIONS MODULE SPECIFICATIONS	39
4.6.1	Session: Object IDs	39
4.6.2	Session: ‘VAT’	39
4.6.3	Session: ‘SmartCharging’	40
4.6.4	PULL Sessions ToIOP: Get List Pagination	40
4.7	CDRS MODULE SPECIFICATIONS	40
4.7.1	CDR: Object IDs	40
4.7.2	CDR content	40
4.7.3	Add billing information in “Remark” field	40
4.7.4	Fields Not Implemented by Gireve	41
4.7.5	PULL CDRs ToIOP: Get List Pagination	41
4.8	TARIFFS MODULE SPECIFICATIONS	41
4.8.1	PULL Tariffs ToIOP: Object ID	42
4.8.2	PULL Tariffs ToIOP: “gireve_id” An Extra Gireve Property	42
4.8.3	PULL Tariffs ToIOP: Tariff Type	42
4.8.4	PULL Tariffs ToIOP: CPO Targeting	42
4.8.5	PULL Tariffs ToIOP: eMSP Targeting	42
4.8.6	PULL Tariffs ToIOP: Get List Pagination	42
4.8.7	Specific properties added by Gireve	43

OCPI Protocol Version Reference

This OCPI Protocol Implementation Guide document is based on OCPI v2.2.1, as defined in document:

- OCPI 2.2.1 Open Charge Point Interface 2.2.1, document version : 2.2.1 : <https://github.com/ocpi/ocpi/tree/release-2.2.1-bugfixes?tab=readme-ov-file>

Related documents

Doc reference	Content	Doc name
OCPI-2.2.1		Open Charge Point Interface 2.2.1, document version : 2.2.1

Document history

Version	Description	Date
1.0	First published version	11/06/2024
1.1	Adding mandatory implementations for CPO Tariff	26/09/2024
1.2	<ul style="list-style-type: none">• Adding eMSP guidelines.• Adding information about Security.• Adding information about EVSE P&C compatibility for the CPO side.• Tariff module mandatory for CPO	28/11/2024

1 Introduction

1.1 Aims

This document describes guidelines to perform a proper connection with Gireve's platform using the OCPI protocol version 2.2.1.

1.2 Intended Audience

This document is dedicated to technical teams (system administrators, developers, etc.) of systems connected or to be connected to Gireve's platform through OCPI.

This document also covers some operational requirements that must be considered when implementing the OCPI 2.2.1 protocol.

1.3 Definitions and Abbreviations

Word	Meaning
IOP	Inter-operation Platform. IOP is the acronym of Gireve's eMobility Services Platform.
RPC	Référentiel des Points de Charge (<i>in French</i>) = Charge Points Repository (<i>in English</i>) The RPC is a system, built around a database that contains Electric Vehicles Charge Infrastructure (EVCI) description. It is connected to IOP. IOP's interfaces (eMIP, OCPI ...) are the only way to access RPC, for partners systems.
ToIOP	Referring to flows for which an operator requests Gireve platform IOP. Partner system is client. IOP is server
FromIOP	Referring to flows for which Gireve platform IOP requests an operator. IOP is client. Partner system is server
Platform	A platform is a backend communicating with IOP through OCPI. A platform can manage one to several operators.
Operator	An operator is a business entity as a CPO or an eMSP and supervised by a platform.
Headers-To	Refers to OCPI 2.2.1 headers "OCPI-to-country-code" and "OCPI-to-party-id"
Headers-From	Refers to OCPI 2.2.1 headers "OCPI-from-country-code" and "OCPI-from-party-id"

1.4 Cardinality expression

To designate the cardinality of fields on data structures the following symbols are used:

Symbol	Description
?	Optional
1	Mandatory
*	0 to n occurrences
+	1 to n occurrences

Gireve's data integration process includes quality controls that ensure the consistency of its data referential. The standard data quality level of Gireve is sustained by numerous mandatory attributes that are not all mandatory by the OCPI standard.

Information and Requirements

- Note that some attributes may not be mandatory by the OCPI standard but are required by Gireve for quality reasons. For further information about the cardinality of attributes by Gireve's quality standard, please refer to the document "Starting roaming operations as a CPO".

2 Integration Guidelines

2.1 Technical

2.1.1 Supported OCPI versions

IOP OCPI implementation supports two versions:

- OCPI 2.1.1
- OCPI 2.2.1

2.1.2 Security

Exchange Authorization Tokens & HTTPS

IOP follows the security standard mechanisms of OCPI. To set up a connection with a new platform, Gireve provides connecting platform with a temporary Token to register. The Token should be used when the connection is initialized by the platform.

In the meantime, the platform can provide Gireve with temporary Token for IOP to initialize the connection. It is not mandatory as the platform is able to launch the Connection & Register process.

During the Connection & Register process, IOP and the platform exchange final Tokens to request each other, and endpoints of their respective OCPI modules.

GIREVE requires all endpoints to be in HTTPS in order to secure communication between the two backends.

IP Filtering

IOP also uses customer IP filtering as an additional security measure. This ensures that only trusted sources can access the API, reinforcing security and protecting against unauthorized access attempts.

Calling partners must provide a list of authorised IP addresses before connecting to the platform.

SSL client certificate security

To enhance security, Gireve configures authentication via SSL client certificates in both directions.

However, only the client certificate used by the partner to send requests to IOP, which is generated by Gireve, is mandatory. The client certificate used by IOP to send requests to the partner, provided by the partner, is optional.

Information and Requirements

- Contrary to OCPI 2.1.1, an OCPI 2.2.1 connection is multi-tenant and multi-role. This means that through a unique connection (i.e. OCPI Handshake) between a platform and IOP, every operator hosted by the platform can communicate with IOP, whatever their role.

- OCPI 2.2.1 requires the Authorization token, sent in headers of every request, to be encoded in base 64.
- Gireve requires all endpoints to be in HTTPS to secure communication between the partner and IOP.
- To secure data exchanges, IOP has an IP filtering for incoming requests.
- To increase security, Gireve is able to configure authentication via SSL client certificate on both ways.

Client certificate, which is mandatory, used by the partner to request IOP is generated by Gireve.

Client certificate used by IOP to request the partner shall be provided by the partner.

2.1.3 Platform and operator identification

OCPI is a protocol enabling the communication between operators (CPO, eMSP, ...).

These operators are technically managed by OCPI platforms.

OCPI platforms are interconnected.

This means that when an operator requests another operator through OCPI, the request must contain the identifiers of the platform that requests, the operator that requests and the operator that is requested.

Information in request used for identification:

Identification of the platform that requests	Identification of the operator that requests	Identification of the requested operator
Authorization Token	Headers-From	Headers-To

Information and Requirements

- The Credentials module and flows are used to manage the OCPI connection between 2 platforms. It doesn't require the usage of Headers-From and Headers-To.
- The usage of Headers-To and Headers-From is mandatory for Gireve, except for Credentials, versions, and versions-details modules.
- Every request shall be sent to IOP operator, using the headers-To. IOP role as a "HUB" is to dispatch the information to other operators.

2.1.4 Traceability: X-Correlation-ID and X-Request-ID

Attributes	Description
X-Request-ID	Every request SHALL contain a unique request ID, the response to this request SHALL contain the same ID. The request ID is the ID of an exchange between two OCPI platforms.
X-Correlation-ID	Every request SHALL contain a unique correlation ID, every response to this request SHALL contain the same ID. The correlation ID is an ID enabling to trace a first request then all exchanges that are "consequences of the first request."

Example: an exchange between a CPO and IOP to update an EVSE status has the same correlation ID as all exchanges between IOP and eMSPs to forward this status update.

Information and Requirements

- Every request sent by a partner to Gireve shall contain a X-Request-ID and a X-Correlation-ID.
- When IOP requests a platform, the platform shall respond using the same X-Request-ID and X-Correlation-ID values.
- Gireve suggests generating and using a UUID for X-Correlation-ID and X-Request-ID values.

2.1.5 Multi-tenant and multi-role capability

An OCPI 2.2.1 connection (i.e. OCPI Handshake) can be used to enable multiple operators to communicate, regardless of their roles.

Information and Requirements

- Only 1 OCPI handshake is needed to initialize the connection and enable the communication between several operators hosted by a unique platform and IOP.
- Gireve configures on its own the roles of an operator and rejects forbidden requests. *Example: If the operator is configured as eMSP only and requests the interface “CDRs Receiver” of IOP, the request is rejected.*

2.1.6 IOP is a “HUB”

Gireve presents the role “HUB” during the Credentials process. A “HUB”, more than a single operator, processes and forwards the incoming request to appropriate targets. Moreover, IOP as a “HUB”, filters and cleans requests between operators.

Examples:

If a CPO is in roaming agreement with X eMSPs through Gireve, the CPO sends only 1 EVSE status update to IOP, then IOP forwards the information to the X eMSPs.

If a CPO sends several times in a row the same EVSE status for an EVSE, IOP takes into account and forwards the first, but ignores the following ones.

Information and Requirements

- IOP country_code is “FR”. Its party_id is “107” on PreProduction and “007” on Production.
- Every request shall be sent to IOP operator, using the headers-To. IOP role as a “HUB” is to dispatch the information to other operators.

2.1.7 Client owned object push

OCPI introduces a specific use of resource identification mechanism, to manage situations where resource belongs to servers and situations where resource belongs to clients. [See OCPI client owned object.](#)

In OCPI 2.2.1, Objects managed through Rest protocol are owned by a CPO, an eMSP, a SCSP or a HUB.

In the same way, for OCPI 2.2.1, there are two « interfaces »: Sender/Receiver.

Module	Who is owner	Who could implement sender interface	Who could implement receiver interface
Credentials	NA	An OCPI platform	An OCPI platform
Locations	CPO, NAP	CPO, NAP, HUB	All roles except CPO
Tokens	EMSP	EMSP, HUB	All roles except EMSP
Commands	NA	EMSP, SCSP, HUB	All roles except EMSP
Sessions	CPO	CPO, HUB	All roles except CPO
CDRs	CPO	CPO, HUB	All roles except CPO
Tariffs	CPO	CPO, HUB	All roles except CPO
ChargingProfiles	EMSP, SCSP	EMSP, SCSP, HUB	All roles
HubClientInfo	HUB	HUB	All roles

Information and Requirements

- Connected to IOP, a platform can receive objects owned by operators behind IOP. The `country_code` and `party_id` of the object owner, in the URL and in the object, are the object owner ones.

2.1.8 Pagination

IOP implements pagination mechanisms described by OCPI. [See OCPI pagination mechanism.](#) IOP requires operators to use pagination when they pull resources requesting IOP. If the operator does not use pagination arguments in its request, IOP will force it answering with the first **X** items and a Link to the second page if any.

2.1.9 Pulling Limits

For each module, IOP has its own max size limit per page. These limits can change with IOP evolutions, the operator implementation might be flexible regarding these limits.

Information and Requirements

- At the moment, IOP limits pulled objects to:
 - Locations module: 20 objects per page
 - Tokens module: 1000 objects per page
 - CDRs module: 20 objects per page
 - Tariffs module: 100 objects per page

2.1.10 List of OCPI modules

Module	Usage	Implemented by Gireve (Yes, No)
Credentials	Initialise and update IT connection information (endpoints, OCPI versions, ...)	Yes
Locations	Transfer charge infrastructure information	Yes
Tokens	Transfer tokens and process Local authorizations	Yes
Commands	Send Commands to CPO (remote start, booking, ...)	Yes

Sessions	Transfer information during charge	Yes
CDRs	Transfer the final charge detail report	Yes
Tariffs	Transfer tariff descriptions	Yes
ChargingProfiles	Transfer charging profiles (smart charge feature)	No
HubClientInfo	Transfer information about connection status to Hub	No

Information and Requirements

- Gireve, in its 1st version of OCPI 2.2.1, has implemented required features for CPOs and eMSPs to do roaming through OCPI 2.2.1. The scope implemented increases with time, updates are published in Gireve release notes and as updates in this document.

2.1.11 Gireve management of Ids

In its OCPI 2.1.1 implementation, Gireve replaces Object Ids sent by object owners by Ids managed by Gireve when objects are transferred to other parties. This transformation is required to ensure Ids unicity.

Example: An eMSP doesn't receive 2 Locations having the same Id if 2 CPOs connected to Gireve identify a Location with the same Id.

Thanks to OCPI 2.2.1 and the adding of object owner identifier in all objects (i.e. "country_code" and "party_id"), parties connected to Gireve in OCPI 2.2.1 receive Ids as sent by object owners in most modules.

Nevertheless, Gireve decides to extend Locations and Tariffs with "gireve_id" property to easier migrations of partners connected through eMIP or OCPI 2.1.1 and which would like to connect on OCPI 2.2.1.

Module	Object Id transferred to receiver in OCPI 2.1.1	Object Id transferred to receiver in OCPI 2.2.1	More information
Locations	Gireve internal Id (i.e. "gireve_id")	Object owner Id	Location object is extended with "gireve_id" when transferred to a receiver party.
Sessions	Gireve internal Id (i.e. "gireve_id")	Gireve internal Id (i.e. "gireve_id")	Gireve internal Id is used in Gireve ecosystem, including the Gireve connect place, to identify a charging session.
CDRs	Gireve internal Id (i.e. "gireve_id")	Object owner Id	-
Tariffs	Gireve internal Id (i.e. "gireve_id")	Object owner Id	Tariff object is extended with "gireve_id" when transferred to a receiver party.

2.2 Gireve management of Locations data

Gireve and its systems distinguish two natures of Location properties:

- Static data: Locations properties which almost never change.

- Dynamic data: Locations properties which can change frequently (e.g., EVSE status, Connector tariff_ids)

All Location properties are considered as static data except for the status of the EVSE, except "REMOVED" and "PLANNED" status, and the tariff_ids attached to a connector.

Information and Requirements


- GIREVE performs a specific process to first integrate static data of CPO Locations in its charge point repository then to integrate static data changes like changes on a Location of a CPO or new Locations or EVSEs. This process implies data quality tests and data completion of the CPO Locations. This process is asynchronous from the standard connection of the CPO with Gireve's IOP platform, meaning that new Locations of the CPO or updates on them can be seen in the Gireve charge point repository several hours after the first PUSH from the CPO to the Gireve IOP platform.

2.3 Roaming


2.3.1 General workflow

An OCPI Roaming session through IOP should run the following workflow.


Authorisation then initialise Session Object



Authorisation then initialise Session Object



Session Status information exchange, stop then Charge Detail Record



2.3.2 Management of B2B tariffs

The CPO connected to Gireve through OCPI have two options to manage and “publish” B2B tariffs:

B2B tariffs are described in roaming agreements: The description and the commitment related to tariffs are contained in roaming agreements signed on Gireve’s Connect Place:

- Tariffs applied for a contract between an eMSP, and a CPO are defined and negotiated, using Gireve’s Connect Place, before signature of the roaming agreement by both parts.

- In case of tariff updates, the CPO and the eMSP must sign an amendment whose management is fully automated.

In this case (tariffs defined in roaming agreements), the CPO should not use the OCPI Tariffs module.

B2B tariffs are not described in roaming agreements: Tariffs are not described in roaming agreements and the CPO transfers them through the OCPI Tariffs module.

- In this case, the CPO manages its tariffs on its own and eMSPs cannot give their insights or validation about applied tariffs.
- In case of tariff updates, the CPO and the eMSP do not need to sign an amendment.

Information and Requirements

- Currently, Gireve has not implemented OCPI 2.2.1 smart charge use-cases. CPOs can send their "FAST", "CHEAP" and "GREEN" tariffs, but they will not be transferred to eMSPs.
- "Ad Hoc" tariffs sent by CPOs are not transferred to eMSPs either.

2.3.3 RFID Tokens

The current typical situation for identification is swiping a MIFARE badge. In this case, the relevant RFID tag in such a situation is a character string that shall contain the **hexadecimal** representation of the 4- or 7-bytes RFID UID (sector 0). Please note that the 7 bytes UID is preferred for interoperability reason.

As an example: "1A2B3C4D5E6F70" shall be interpreted as

- Lowest address byte contains "1A" and "1" is the most significant nibble (half byte) and "A" is the least significant nibble.
- Highest address byte contains "70".
- Equivalent decimal value is "7365887390543728".

The RFID is not case sensitive. We recommend using uppercase characters. Leading zeros must be provided to reach 8 characters in case of 4 bytes UID or 14 characters in case of 7 bytes UID.

Information and Requirements

- For safety reasons, IOP rejects requests done with a bad RFID UID format.

3 CPO Specific Implementation Guidelines

3.1 General information

3.1.1 CPO operation definition and naming rules

A CPO operation is a homogeneous group of charging points. A CPO operation is defined by its unique eMI3 operation code also called "Operator Id" which is composed by a 2 ALPHA country code plus a 3 ALPHANUMERIC Spot Operator ID.

Example: FR*AB1

eMI3 standard official documentation can be downloaded here:
<https://emi3group.com/documents-links/>

All EVSE included in each CPO operation must have an evse_id following the eMI3 standard naming rules defined in this specific document, page 27:

<https://emi3group.com/wp-content/uploads/sites/5/2018/12/eMI3-standard-v1.0-Part-2.pdf>

Specifically, all evse_id included into a given operation must always start with the Operator Id.

Example: FR*AB1*EABCDEFG*1

Information and Requirements

- It is not allowed to include in each CPO operation evse_ids starting with a different Operator-Id.
*Example: A CPO "DE*CPO" having an "evse_id" not starting by "DECPO" or "DE*CPO" is not allowed*

3.1.2 CPO operation and roaming offers

A CPO Operation is the smallest entity that can constitute a roaming offer.

Although Gireve's technical platform (IOP) is built to manage bilateral communications between 1 operation (i.e. CPO) and another (i.e. eMSP), it is possible to aggregate several operations into a so-called network group on Gireve's Connect Place. It allows to publish a single roaming offer that includes several operations. The main advantages of such an offer structure are:

- Reduces the number of roaming agreements (1 agreement instead of several bilateral contracts – one per operation).
- Allows to add or remove operations from the network without terminating the current agreement or issuing amendments, enabling new tenants to benefit from already active roaming agreements.

3.2 Use cases covered by IOP

OCPI features are composed by several use cases that a CPO can choose to implement or not when connecting to an operator. In case of connection to Gireve, here is the list of use cases that a CPO can implement:

Use Case Family	Use case	Web Service
Credentials	Register - FromIOP	Get FromIOP_versions
		Get FromIOP_version-details
		Get ToIOP_versions
		Get ToIOP_version-details
		POST FromIOP_credentials
	<i>Register - ToIOP (*)</i>	Get FromIOP_versions
		Get FromIOP_version-details
		Get ToIOP_versions
		Get ToIOP_version-details
		<i>POST ToIOP_credentials (*)</i>
<i>Update Credentials - ToIOP</i>	<i>PUT ToIOP_credentials</i>	
<i>Update Credentials - FromIOP</i>	<i>PUT FromIOP_credentials</i>	
Unregister - FromIOP	DELETE FromIOP_credentials	
<i>Unregister - ToIOP</i>	<i>DELETE ToIOP_credentials</i>	
Locations	Push EVCI - ToIOP	PUT ToIOP_receiver_locations
		PUT ToIOP_receiver_locations-evse
		<i>PUT ToIOP_receiver_locations-evse-connector</i>
	Update EVCI - ToIOP	PATCH ToIOP_receiver_locations
		PATCH ToIOP_receiver_locations-evse
		<i>PATCH ToIOP_receiver_locations-evse-connector</i>
	Pull EVCI - FromIOP	GET FromIOP_sender_locations
	<i>Check EVCI</i>	<i>GET ToIOP_receiver_locations</i>
<i>GET ToIOP_receiver_locations-evse</i>		
<i>GET ToIOP_receiver_locations-evse-connector</i>		
<i>Tokens exchange</i>	<i>Pull Tokens - ToIOP</i>	<i>GET ToIOP_sender_tokens</i>

	<i>Push Tokens - FromIOP</i>	<i>PUT FromIOP_receiver_tokens</i> <i>PATCH FromIOP_receiver_tokens</i>
Local Authorization (Requested by CPO)	Real-Time Authorization - ToIOP	POST ToIOP_sender_tokens-authorize
Remote Authorization (Requested by eMSP)	Remote start - FromIOP	POST FromIOP_receiver_commands_START_SESSION POST ToIOP_sender_commands_START_SESSION-Callback
	Remote stop - FromIOP	POST FromIOP_receiver_commands_STOP_SESSION POST ToIOP_sender_commands_STOP_SESSION-Callback
Sessions	Push Sessions - ToIOP	PUT ToIOP_receiver_sessions <i>PATCH ToIOP_receiver_sessions</i>
	<i>Pull Sessions - FromIOP</i>	<i>GET FromIOP_sender_sessions</i>
	<i>Check Sessions - ToIOP</i>	<i>GET ToIOP_receiver_sessions</i>
	<i>Push Sessions -FromIOP (smart charging)</i>	<i>PUT FromIOP_sender_sessions-charging_preferences</i>
CDR	Push CDRs - ToIOP	POST ToIOP_receiver_cdrs
	<i>Pull CDRs - FromIOP</i>	<i>GET FromIOP_sender_cdrs</i>
	<i>Check CDRs - ToIOP</i>	<i>GET ToIOP_receiver_cdrs</i>
	<i>CreditCDRs - Any</i>	-
Tariffs	Push Tariffs - ToIOP	PUT ToIOP_receiver_tariffs
	<i>Pull Tariffs - FromIOP</i>	<i>GET FromIOP_sender_tariffs</i>
	<i>Delete Tariffs - ToIOP</i>	<i>DELETE ToIOP_receiver_tariffs</i>
	<i>Check Tariffs - ToIOP</i>	<i>GET ToIOP_receiver_Tariffs</i>
Hub Client Info	<i>PUSH Hub Client Info - FromIOP</i>	<i>PUT FromIOP_receiver_clientinfo</i>
	<i>PULL Hub Client Info - FromIOP</i>	<i>GET ToIOP_sender_clientinfo</i>
Booking	Reserve now - FromIOP	POST FromIOP_receiver_commands_RESERVE_NOW POST ToIOP_sender_commands_RESERVE_NOW-Callback
	Cancel reservation - FromIOP	POST FromIOP_receiver_commands_CANCEL_RESERVATION POST ToIOP_sender_commands_CANCEL_RESERVATION-Callback
Commands	Unlock Connector - FromIOP	POST FromIOP_receiver_commands_UNLOCK_CONNECTOR POST ToIOP_sender_commands_UNLOCK_CONNECTOR-Callback

(*) Not yet implemented by IOP

3.3 Use cases required by Gireve

Some use cases are required when connecting to Gireve

Always required

Use case	Why?
Register – FromIOP Or Register - ToIOP	These use cases are needed to initialise connection between a platform and IOP
Push EVCI - ToIOP	A CPO connected to Gireve must transfer “in real time” EVSE status changes of its EVSEs and tariff_ids of its Connectors
Pull EVCI - FromIOP	Gireve wants to be able to refresh EVCI data when needed.

If the CPO implements the “Roaming” feature

Use case	Why?
Real-Time Authorization - ToIOP	A CPO should be able to request eMSP through IOP when a driver uses his RFID badge or a P&C Contract certificate to charge.
Remote start - FromIOP	Remote authorisation and start features on CPO infrastructure are required by Gireve
Remote stop - FromIOP	Remote stop features on CPO infrastructure are required by Gireve
Push Sessions - ToIOP	A CPO must be able to send information about charging-sessions through Session objects (charge started, ...)
Push CDRs - ToIOP	The CPO must send the CDR in real time after the end of the charging-session.
Push Tariffs - ToIOP	CPOs must inform in real-time, through IOP, eMSPs about tariff changes.

Information and Requirements

- The implementation and certification of the OCPI Tariffs module depends on the tariff's strategy of the CPO. It is not required if the CPO describes its tariffs through the Gireve connect place.
- CDRs shall be sent as soon as possible after the end of the charge.

3.4 Connection & Register specifications

IOP follows the OCPI 2.2.1 standard for Connection & Register process. [See OCPI 2.2.1 specifications.](#)

The Credentials module is used to manage the OCPI connection between 2 OCPI platforms. It doesn't require the usage of Headers-From and Headers-To because it is not used for an operator to communicate.

Unlike OCPI 2.1.1, the Authorization token shall be base 64 encoded in OCPI 2.2.1.

Also, Gireve presents the role "HUB" and will only presents the Operator FR*007 (Production environment) and or FR*107 (Preproduction environment).

Information and Requirements

- Gireve has not implemented the "update Credentials". To update the OCPI connection information (i.e. Authorization Token and/or endpoints) the platform shall unregister with IOP then register again.
- During the registration process, a Partner can present a list of operators, but it will be ignored by IOP. Gireve manually creates/integrates the various operators (**who have contracted with Gireve**) a Partner can manage.
- Only 1 OCPI handshake is needed to initialise the connection and enable the communication between several operators hosted by a unique platform and IOP.
- The usage of Headers-To and Headers-From is mandatory for Gireve, except for Credentials module.
- Gireve has only implemented the "Register – FromIOP" and "Unregister – FromIOP" use cases.

3.5 Locations module specifications

IOP follows the OCPI 2.2.1 standard for Locations upload by a CPO. [See OCPI 2.2.1 specifications.](#)

3.5.1 Locations information required by Gireve

Gireve requires some information to be filled by CPOs in Locations data, even if they are optional in the OCPI 2.2.1 standard. This information is used to ensure data quality.

List of the required properties

Property	Reason
owner.name	Used to fill the information about the owner of the land where the charging station is located. The owner can also manage the charging station.
operator.name	Used to fill the "brand name" information
evses.connectors.tariff_ids	Used to dispatch EVSEs per tariff groups, even in case Tariffs are described through the Gireve's connect place.
evses.capabilities	Used to know, among others, if the EVSE is RFID or remote start capable.

3.5.2 Static and dynamic attributes

The attributes of the Location object are of 2 types:

- Static attributes are data attributes that do not change frequently (address, localisation ...). These data are integrated in Gireve database through the Gireve quality process and could take some time before to be stored by Gireve and displayed to eMSPs.
- Dynamic attributes are data attributes that may change frequently (availability, occupied/free ...). In OCPI 2.2.1, only "EVSE.status" and "Connector.tariff_ids" are considered as dynamic. These data are integrated in real-time by Gireve when CPOs send updates to IOP.

3.5.3 "tariff_ids" property

Gireve uses the "tariff_ids" information provided by CPOs in Locations to dispatch CPO's EVSEs into separated EVSE tariff groups. Also, CPOs can refer to these tariff groups when they describe tariffs directly in their roaming offer via Gireve's connect place.

If CPOs use the OCPI Tariffs module to send their tariffs, the management of tariffs and relations to the charging infrastructure follows the OCPI standard except that in Gireve systems, tariffs are linked to EVSEs and not to connectors.

In its current implementation of OCPI 2.2.1, Gireve stores all tariffs coming from CPOs, whatever their nature, but transfers only "B2B Regular" tariffs to eMSPs, whatever their protocol.

3.5.4 “publish” property

The “publish” information, added in OCPI 2.2.1 on Locations level, is used by CPO to inform other parties that the Location shall not be displayed on any support (i.e. a map on mobile application, ...).

As this information doesn't exist in OCPI 2.1.1, Gireve doesn't send Locations with “publish” value false to eMSPs connected to IOP in OCPI 2.1.1.

3.5.5 Plug&Charge (P&C)

The ability to enable Plug & Charge (P&C) functionality, eliminating the need for a physical badge, offers a significant improvement in the user experience for EV drivers.

Gireve has implemented a mechanism allowing CPOs to inform eMSPs about EVSE compatibility with Plug & Charge by introducing two new capabilities at the EVSE level:

OCPI Field	Enum	Description
Location.evse.capabilities	ISO_15118_2_PLUG_AND_CHARGE	Compatibility of an EVSE with P&C using ISO15118-2
Location.evse.capabilities	ISO_15118_20_PLUG_AND_CHARGE	Compatibility of an EVSE with P&C using ISO15118-20

3.5.6 Store and Forward – PUT and PATCH Locations

A Store and Forward mechanism shall be implemented by CPOs to ensure that no data upload may be lost, in case of a connection loss. Any data upload that didn't get a correct response (HTTP code: 2xx) from Gireve IOP platform must be stored on CPO side and a retry process must be active. After the connection recovery, the Data Upload messages must be resent in a FIFO manner.

Information and requirements

- Locations static data follow a quality process before they are integrated in Gireve's repository, meaning that Locations creation, update or deletion could take some time before being integrated by Gireve then displayed to other parties.
- As a reminder, the "evse_id" property is mandatory except if the EVSE has status "REMOVED". Moreover, this property containing the eMI3Id of the EVSE shall begin by the eMI3Id of the CPO.
- "connectors.tariff_ids", "owner.name", "operator.name" and "evses.capabilities" are mandatory for Gireve.
- Locations having "publish" flag set to false are not transferred to parties connected to Gireve in OCPI 2.1.1 protocol.
- In Gireve's model, the tariff is attached to the EVSE level and not to the connector level as in OCPI. IOP keeps "tariff_ids" attached to the first connector of the EVSE in the payload and applies them to the EVSE. "tariff_ids" of other connectors are ignored.
- A CPO shall retry every PUT and PATCH Locations in case of a technical error (i.e. timeout, http return code different than 2xx, ...)

3.6 Tokens module specifications

IOP follows the OCPI standard for Tokens module. [See OCPI 2.2.1 specifications.](#)

3.6.1 Download of Tokens not recommended

Unlike OCPI 2.1.1, CPOs connected to Gireve in OCPI 2.2.1 don't need to download the whole list of eMSP Tokens.

In case they don't know the Token, the CPO requests IOP with a "POST Tokens-authorize" then receive the full description of the Token if the eMSP is connected to Gireve.

For this reason, Gireve doesn't include the download of Tokens by CPOs in its current implementation of OCPI 2.2.1.

3.6.2 "LocationReferences" mandatory in POST Tokens Authorize requests

As in OCPI 2.1.1, when requesting authorization, the CPO:

- Must specify 1 Location.
- Can set 0 to N EVSEs in its request. Gireve will select 1 and only 1 to continue the authorization request.

Information and requirements

- Gireve suggests that CPOs do not download Tokens of eMSPs and to send a POST Tokens authorize request in case of unknown Tokens. For this reason, Gireve doesn't include the download of Tokens by CPOs in its current implementation of OCPI 2.2.1.

- The POST Tokens authorize request shall contain the reference to a Location.

3.7 Commands module specifications

IOP follows the OCPI standard for Commands received by a CPO. [See OCPI specifications.](#)

3.7.1 List of available Commands

Command	Available?
START_SESSION	Yes
STOP_SESSION	Yes
RESERVE_NOW	No
CANCEL_RESERVATION	No
UNLOCK_CONNECTOR	No

3.7.2 New field “connector_id” in START_SESSION

A new field “connector_id” was added to the START_SESSION request in OCPI 2.2.1. As it is not present in OCPI 2.1.1, eMSPs connected to IOP in OCPI 2.1.1 are not able to send this information, even if it is mandatory for CPO.

3.8 Sessions module specifications

IOP follows the OCPI standard for Sessions sent by a CPO. [See OCPI 2.2.1 specifications.](#)

3.8.1 Session initialisation

The CPO shall initialize a Session (i.e. send a PUT Session) after an allowed authorization and when the EV plugs to the EVSE. This flow gives information to eMSP that the charge session of its customer has started.

3.8.2 Smart charging use cases

In its current implementation of OCPI 2.2.1, Gireve has not implemented smart charging use cases. An operator is not able to send its “Charging Preferences” on an ongoing charging session.

3.8.3 PATCH Sessions

Although Gireve has not implemented PATCH Sessions In its current OCPI 2.2.1 implementation, it is recommended for CPOs to send PATCH Sessions.

Connected partners won't have to change their OCPI implementation when Gireve makes the PATCH Sessions available.

3.8.4 Store and forward – PUT Sessions

A Store and Forward mechanism must be implemented to ensure that no Session may be lost, in case of a connection loss. Any PUT session that didn't get a correct response (HTTP code: 2xx) from Gireve IOP platform must be stored on the CPO's side and a retry process must be active. After the connection recovery, the session messages must be resent in a FIFO manner.

3.8.5 Advenir specific use case

Gireve enables CPOs to use their connection to IOP to transfer their consumption information (i.e. Sessions and CDRs) to the French subsidy program Advenir.

If used, CPOs shall send all consumption information of the charging station to IOP, even if it is not a roaming charge.

In case it is not a roaming charge, the CPO shall anonymise Sessions and CDRs with the following values

Attribute	Value
CdrToken.country_code	\$\$(*)
CdrToken.party_id	ADV(*)
CdrToken.uid	12345671234567(*)
CdrToken.type	RFID(*)
CdrToken.contract_id	Gireve2Advenir(*)

(*) Information to confirm by Gireve during onboarding

Information and requirements

- Unlike Locations and Tariffs where IOP forwards CPO Ids to eMSPs, Session Ids and authorization references are replaced by Gireve ones.
This decision has been made to ensure the consistency with other protocols and Gireve systems.
- "PATCH Sessions" webservice has not been implemented in the Gireve current implementation. Nevertheless, it is recommended that CPOs already implement and use them.
- Session updates shall be stored and forwarded to Gireve in case of a technical error.
- Gireve billing feature doesn't consider or calculate VAT. In case costs are calculated by Gireve and included in Sessions/CDRs, VAT information is not filled.

3.9 CDRs module specifications

IOP follows the OCPI standard for Sessions sent by a CPO. [See OCPI 2.2.1 specifications.](#)

3.9.1 CDR sending frequency

Gireve requires CDRs to be sent directly at the end of the charging-session.

eMSPs will therefore be able to display the charging-session price directly to their end customers.

3.9.2 CDR content

The "total_time" value is the total duration of this session (including the duration of charging and not charging).

It doesn't include the duration during which the EVSE is out of order so cannot supply the service. The out of order duration should be free of charge for eMSPs.

3.9.3 CreditCDR

Although Gireve has not implemented Credit CDRs use cases in its current OCPI 2.2.1 implementation, it is recommended for CPOs to manage and send them.

Connected partners won't have to change their OCPI implementation when Gireve makes this use case available.

3.9.4 Store and forward – POST CDRs

Similarly to a PUT sessions, Store and Forward mechanism must be implemented to ensure that no CDR can be lost, in case of a connection loss. Any POST Cdrs that didn't get a correct response (i.e. HTTP code: 2xx) from the Gireve platform IOP must be stored on CPO side and a retry process must be active. After the connection recovery, the Cdr messages must be resent in a FIFO manner.

3.9.5 Advenir specific use case

Gireve enables CPOs to use their connection to IOP to transfer their consumption information (i.e. Sessions and CDRs) to the French subsidy program Advenir.

If used, CPOs shall send all consumption information of the charging station to IOP, even if it is not a roaming charge.

In case it is not a roaming charge, the CPO shall anonymise Sessions and CDRs with the following values

Attribute	Value
CdrToken.country_code	\$\$(*)
CdrToken.party_id	ADV(*)
CdrToken.uid	12345671234567(*)
CdrToken.type	RFID(*)
CdrToken.contract_id	Gireve2Advenir(*)

(*) Information to confirm by Gireve during onboarding

Information and requirements

- Unlike Locations and Tariffs where IOP forwards CPO Ids to eMSPs, "Session Ids" and "authorization references" are replaced by Gireve ones. This decision has been made to ensure consistency with other protocols and Gireve systems.
- "Credit CDR" use case has not been implemented in Gireve's current implementation. Nevertheless, it is recommended that CPOs already implement and use them.
- CDRs shall be stored and forwarded to Gireve in case of technical error.
- Gireve billing feature doesn't consider or calculate VAT. In case costs are calculated by Gireve and included in Sessions/CDRs, VAT information is not filled.

3.10 Tariffs module specification

IOP follows the OCPI standard for Tariffs upload by a CPO. [See OCPI specifications.](#)

3.10.1 Locations tariff update

In case of tariff changes on a Location, Gireve suggests CPOs:

- Create a new Tariff with “start_date” at the date of the change.
- Update the “end_date” of the ongoing tariff.
- Attach the connectors to both tariffs, current one and next one.

3.10.2 Tariff shall be immutable

Management of tariffs is complex for CPOs and eMSPs, especially when tariff description changes (i.e. same tariff_id, different description). That's why Gireve suggests CPOs never change tariff properties attached to the price calculation.

The only information that can change shall be textual properties or end_date.

3.10.3 Tariff information required by Gireve

Gireve requires some information to be filled by CPOs in Tariff data, even if they are optional in the OCPI 2.2.1 standard. This information is used to ensure data quality.

List of the required properties

Property	Reason
start_date_time	<p>The CPO must send us a start_date_time to indicate the date from which the tariff applies. the tariff start_date_time is used to bill sessions with tariffs that apply when the session is active.</p> <p>If the CPO does not send us a start_date_time, the date of reception will be the start of the tariff's applicability.</p> <p>Example:</p> <ul style="list-style-type: none"> • There was a bug on 09/25 in the CPO system, so we didn't receive the tariffs applicable on 09/25, nor the sessions.

- The CPO returned the same tariffs on 26/09 without start_date_time, so we set start_date_time to 26/09.
- The charge sessions of 25/09 cannot be billed with these tariffs as they are applicable from 26/09.

3.10.4 Differentiate tariff per eMSP

For some reason, a CPO might want to define different tariffs for a unique Location depending on the eMSP.

Example: For eMSP A on connector X, the "B2B Regular" tariff is 1€/h. For all other eMSPs, the tariff is 1,20€/h.

The connection to a Hub is not compatible with this use case, that's why Gireve has extended the Tariff object in OCPI 2.2.1 with 2 optional properties:

Attribute	Card.	Description
target_operator_country_code	?	Country code of the eMSP this tariff applies to. Shall be filled if target_operator_party_id is filled
target_operator_party_id	?	Party Id of the eMSP this tariff applies to. Shall be filled if target_operator_country_code is filled

This behaviour works with the following main principles:

- "tariff_ids" attached to a connector are the same, whatever the eMSP.
- For a single "tariff_id", the description of the tariff (OCPI 2.2.1 Tariffs module) can be different according to the eMSP.
- If "target_operator_country_code" and "target_operator_party_id" are null, the tariff description applies to all eMSPs (i.e. default tariff).
- When a CPO is pulled by IOP to get tariffs, it shall respond with multiple iterations for a single "tariff_id", one for each tariff description.

Example:

CPO FR*CPO pushes 3 times tariff "tariff_A":

tariff id	Description	target_operator_country_code and target_operator_party_id values
tariff_A	0,50€/h	DE MP1
tariff_A	0,10€/kWh	NL MP2
tariff_A	0,80€/h	-

"tariff_A" is 0,80€/h for all eMSPs

Except for eMSP NLMP2 for which "tariff_A" is 0,10€/kWh

And for eMSP DEMP1 for which "tariff_A" is 0,50€/h

3.10.5 Tariffs are attached to the EVSE level

In Gireve's model, the tariff is attached to the EVSE level and not to the connector level. IOP keeps "tariff_ids" attached to the first connector of the EVSE in the payload and applies them to the EVSE. "tariff_ids" of other connectors are ignored.

3.10.6 Store and forward – PUT Tariffs

Similarly to a POST Cdrs, Store and Forward mechanism must be implemented to ensure that no Tariffs can be lost, in case of a connection loss. Any PUT Tariffs that didn't get a correct response (HTTP code: 2xx) from Gireve IOP platform must be stored on CPO side and a retry process must be active. After the connection recovery, the Tariffs messages must be resent in a FIFO manner. eMSP Specific Implementation Guidelines.

Information and requirements



- In Gireve's model, the tariff is attached to the EVSE level and not to the connector level. IOP keeps "tariff_ids" attached to the first connector of the EVSE in the payload and applies them to the EVSE. "tariff_ids" of other connectors are ignored.
- Gireve extends "Tariff" object with 2 new properties target_operator_country_code and target_operator_party_id enabling a CPO to differentiate tariff description per eMSP. See [3.10.4 Differentiate tariff per eMSP](#).
- A tariff shall be immutable, that's why Gireve suggests CPOs never update a tariff description, except for text properties and "end_date".

4.1 Use cases covered by IOP

OCPI features are composed by several use cases that an eMSP can choose to implement or not when connecting to an operator. In case of connection to Gireve, here is the list of use cases that an eMSP can implement:

Use Case Family	Use case	Web Service
Credentials	Register - FromIOP	Get FromIOP_versions
		Get FromIOP_version-details
		Get ToIOP_versions
		Get ToIOP_version-details
		POST FromIOP_credentials
		POST ToIOP_credentials
	<i>Register - ToIOP</i>	Get FromIOP_versions
		Get FromIOP_version-details
		Get ToIOP_versions
		Get ToIOP_version-details
		<i>POST ToIOP_credentials</i>
		<i>PUT ToIOP_credentials</i>
<i>Update Credentials - ToIOP</i>	<i>PUT ToIOP_credentials</i>	
<i>Update Credentials - FromIOP</i>	<i>PUT FromIOP_credentials</i>	
Unregister - FromIOP	DELETE FromIOP_credentials	
<i>Unregister - ToIOP</i>	<i>DELETE ToIOP_credentials</i>	
Locations	<i>Push EVCI (static data) - FromIOP</i>	<i>PUT FromIOP_receiver_locations</i>
		<i>PUT FromIOP_receiver_locations-evse²</i>
		<i>PUT FromIOP_receiver_locations-evse-connector</i>
		<i>PATCH FromIOP_receiver_locations</i>
		<i>PATCH FromIOP_receiver_locations-evse</i>
		<i>PATCH FromIOP_receiver_locations-evse-connector</i>
	Push EVCI (dynamic data) - FromIOP	<i>PATCH FromIOP_receiver_locations-evse</i>
		<i>PATCH FromIOP_receiver_locations-evse-connector</i>

	Pull EVCI – ToIOP (all CPOs)	GET ToIOP_sender_locations
	Pull EVCI - ToIOP (1 CPO)	GET ToIOP_sender_locations (using the headers “ocpi-to-country-code” and “ocpi-to-party-id”)
	<i>Pull EVCI by Id - ToIOP</i>	GET ToIOP_sender_locations/id
		GET ToIOP_sender_locations-evse/id
		GET ToIOP_sender_locations-evse-connector/id
Tokens exchange	Push Tokens - ToIOP	PUT ToIOP_receiver_tokens
		PATCH ToIOP_receiver_tokens
	<i>Pull Tokens - FromIOP</i>	GET FromIOP_sender_tokens
Local Authorization (Requested by CPO)	Real-Time Authorization - FromIOP	POST FromIOP_sender_tokens-authorize
Remote Authorization (Requested by eMSP)	Start Session - ToIOP	POST ToIOP_receiver_commands_START_SESSION
		POST FromIOP_sender_commands_START_SESSION-Callback
	Stop Session - ToIOP	POST ToIOP_receiver_commands_STOP_SESSION
		POST FromIOP_sender_commands_STOP_SESSION-Callback
Sessions	Push Sessions - FromIOP	PUT FromIOP_receiver_sessions
	<i>Pull Sessions - ToIOP</i>	GET ToIOP_sender_sessions
	<i>Push Sessions – ToIOP (smart charging)</i>	PUT ToIOP_sender_sessions-charging_preferences
CDR	Push CDRs - FromIOP	POST FromIOP_receiver_cdrs
	<i>Pull CDRs - ToIOP</i>	GET ToIOP_sender_cdrs
	<i>CreditCDRs – Any</i>	-
Tariffs	<i>Push Tariff - FromIOP</i>	PUT FromIOP_receiver_tariffs
	Pull Tariffs – ToIOP (all CPOs)	GET ToIOP_sender_tariffs
	Pull Tariffs – ToIOP (1 CPO)	GET ToIOP_sender_tariffs (using the headers “ocpi-to-country-code” and “ocpi-to-party-id”)
Hub Client Info	<i>PUSH Hub Client Info - FromIOP</i>	PUT FromIOP_receiver_clientinfo
	<i>PULL Hub Client Info - FromIOP</i>	GET ToIOP_sender_clientinfo
Booking		POST ToIOP_receiver_commands_RESERVE_NOW
	<i>Reserve now - FromIOP</i>	POST FromIOP_sender_commands_RESERVE_NOW-Callback

	<i>Cancel reservation - FromIOP</i>	<i>POST ToIOP_receiver_commands_CANCEL_RESERVATION</i>
		<i>POST FromIOP_sender_commands_CANCEL_RESERVATION-Callback</i>
Commands	Unlock Connector – FromIOP	<i>POST ToIOP_receiver_commands_UNLOCK_CONNECTOR</i>
		<i>POST FromIOP_sender_commands_UNLOCK_CONNECTOR-Callback</i>

4.1.1 Use cases required by Gireve

Some use cases are required when connecting to Gireve.

Always required

Use case	Why?
Register – FromIOP Or Register - ToIOP	These use cases are needed to initialise connection between a platform and IOP

If the eMSP implements the “Roaming” feature

Use case	Why?
Push CDRs - FromIOP	eMSP shall be able to receive CDRs
Push Tokens – ToIOP	eMSP Tokens shall be uploaded to IOP to enable roaming with CPOs connected through OCPI 2.1.1

Information and Requirements

- eMSP tokens must be uploaded to the IOP to enable roaming with CPOs connected via OCPI 2.1.1.
- eMSPs must always be able to receive CDRs sent by CPOs as soon as possible after the end of the charge.

4.2 Connection & Register specifications

IOP follows the OCPI 2.2.1 standard for Connection & Register process. [See OCPI 2.2.1 specifications.](#)

[See](#) Connection & Register specifications

Information and Requirements

- Gireve has not implemented the “update Credentials”. To update the OCPI connection information (i.e. Authorization Token and/or endpoints) the platform shall unregister with IOP then register again.
- During the registration process, a Partner can present a list of operators, but it will be ignored by IOP. Gireve manually creates/integrates the various operators (**who have contracted with Gireve**) a Partner can manage.
- Only 1 OCPI handshake is needed to initialise the connection and enable the communication between several operators hosted by a unique platform and IOP.
- The usage of Headers-To and Headers-From is mandatory for Gireve, except for Credentials module.
- Gireve has only implemented the “Register – FromIOP” and “Unregister – FromIOP” use cases.

4.3 Locations module specifications

IOP follows the OCPI standard for Locations downloaded by an eMSP. [See OCPI 2.2.1 specifications.](#)

4.3.1 Static and dynamic attributes

See [Static and dynamic attributes](#)

4.3.2 PULL Locations: Retrieve Locations of a single given CPO

When an eMSP requests IOP to get Locations, IOP responds with Locations of every CPOs the eMSP is in contract with.

In some cases, eMSPs need only Locations of a specific CPO. For example, when the eMSP initializes data of a CPO after signature of a new roaming agreement.

This use case is open to eMSPs by filling the 2 headers “ocpi-to-country-code” and “ocpi-to-party-id” by CPO’s country_code and party_id.

4.3.3 PULL Locations ToIOP: Get List, Full and Delta modes

If the eMSP wants to retrieve all the Locations, it should not include « date_from » and/or « date_to » parameters in its request. But if it wants to get only changes (optimised), it should use it.

NB: The Location and EVSE deletion logic is different if using « date_from » and/or « date_to » parameters or not. When « date_from » and/or « date_to » are present, the eMSP get EVSEs of the Location in status « REMOVED » whereas without « date_from » and/or « date_to » parameters the deleted items are not included in the response (see table below).

For information, when eMSP PULL Locations list from IOP, IOP follows the below logic in responses provided:

	LOCATION	EVSE	CONNECTOR
CREATE	New Location is part of the response.	New EVSE is part of the response.	New Connector is part of the response.
UPDATE	Updates are parts of the response.	Updated EVSE is part of the response.	Updated Connector is part of the response.
DELETE	<ul style="list-style-type: none"> - Using « date_from » and/or « date_to » option, response contains all EVSEs of the Location with « REMOVED » value for « status » field. - Without « date_from » and/or « date_to » option, the response does not contain this Location. 	<ul style="list-style-type: none"> - Using « date_from » and/or « date_to » option, response contains the EVSE with « REMOVED » value for « status » field. - Without « date_from » and/or « date_to » option, the response does not contain this EVSE. 	Deleted Connectors are not part of the response.

If the eMSP wants to retrieve a list of Locations, it can call the URL: /ocpi/sender/2.2.1/locations?date_from= using the paginated properties date_from, date_to, offset and limit.

Parameters « offset » and « limit » are optional but IOP always returns a paginated response (subset of objects list and link, X-Total-Count and X-limit headers).

The eMSP must call **the link returned in the headers** to get the next pages.

IOP has its own max limit (**100 Locations**) and answers with its if the client limit is upper than IOP one or the client doesn't set its limit.

4.3.4 PULL Locations ToIOP: evse_id

It may happen that evse_id may not be compliant with the eMI3 standard. In this case, **you should not reject** them because of the non-compliance with the standard.

4.3.5 PULL Locations ToIOP: "gireve_id" An Extra Gireve Property

In **OCPI 2.1.1**, Gireve uses its internal ID (Gireve ID) to identify a location, EVSE, or connector when transmitting location data to an eMSP.

In **OCPI 2.2.1**, the availability of the **country_code** and **party_id** fields allows the eMSP to identify the CPO owning the location. As a result, Gireve will send external IDs, as provided by the CPO in the OCPI fields, instead of internal IDs to eMSPs connected via OCPI 2.2.1.

In addition to the external ID, Gireve will also include a new field (not part of the OCPI protocol), called gireve_id, for each of the following elements: **Location / EVSE / Connector**. It is useful for an eMSP upgrading from OCPI 2.1.1 to OCPI 2.2.1 to reconcile the location data received via these two protocols.

4.3.6 PULL Locations ToIOP: tariff_ids

When the eMSP download the locations, it receives only tariffs_id with the type "REGULAR" (B2B) and they are mapped with external_id of tariff(s) as sent by CPOs.

4.3.7 PULL Locations ToIOP: Plug&Charge (P&C)

The ability to enable Plug & Charge (P&C) functionality, eliminating the need for a physical badge, offers a significant improvement in the user experience for EV drivers.

Gireve has implemented a mechanism allowing CPOs to inform eMSPs about EVSE compatibility with Plug & Charge by introducing two new capabilities at the EVSE level:

OCPI Field	Enum	Description
Location.evse.capabilities	ISO_15118_2_PLUG_AND_CHARGE	Compatibility of an EVSE with P&C using ISO15118-2

Location.evse.capabilities ISO_15118_20_PLUG_AND_CHARGE	Compatibility of an EVSE with P&C using ISO15118-20
--	---

eMSPs **should accept these two new capabilities** when they are provided by Gireve.

4.3.8 PULL Locations ToIOP: Connector Standards

Gireve supports all connector standards, including US types, and ensures they are communicated to eMSPs.

4.3.9 Fields Not Implemented by Gireve

[Publish_allowed_to](#)

The “publish_allowed_to” field is not implemented by Gireve; therefore, eMSPs will not receive it. Instead, eMSPs will only receive the publish field for a location.

eMSPs may comply with the OCPI requirement for a publish false Location and not publish it.

[Opening_times.exeptional_openings](#)

The “exceptional_openings” field of the “Opening_times” object is not implemented by Gireve; therefore, eMSPs will not receive it.

[Charging_when_closed](#)

The “charging_when_closed” field is not implemented by Gireve; therefore, eMSPs will not receive it.

[Images](#)

The “images” field is not implemented by Gireve; therefore, eMSPs will not receive it.

[Energy_mix](#)

The “energy_mix” field is not implemented by Gireve; therefore, eMSPs will not receive it.

4.3.10 PUSH Locations FromIOP

When the status of an EVSE changes, the CPO will send the update to Gireve dynamically.

Gireve then forwards the dynamic status changes of the EVSE using the external IDs of the location and EVSE. The uniqueness of these IDs is guaranteed by the combination of the country_code and party_id of the CPO in the request URL.

Information and Requirements

- By filling the 2 headers “ocpi-to-country-code” and “ocpi-to-party-id” by the CPO's country_code and party_id, the eMSP is able to retrieve only the locations of this specific CPO.
- The Location and EVSE deletion logic is different if using « date_from » parameter or not. When « date_from » is present, the eMSP get EVSEs of the Location in status « REMOVED » whereas without « date_from » the deleted items are not included in the response.

- In addition to the CPO system ID, Gireve will also include a new field called `gireve_id` for each location, EVSE, and connector.
- When the eMSP downloads the locations, it receives only the `tariff_id` with the type "REGULAR" (B2B), and these are mapped with the tariff ID(s) as sent by the CPOs.
- Gireve has implemented a mechanism allowing CPOs to inform eMSPs about EVSE compatibility with Plug & Charge by introducing two new capabilities at the EVSE level: `Location.evse.capabilities.ISO_15118_2_PLUG_AND_CHARGE` and `Location.evse.capabilities.ISO_15118_20_PLUG_AND_CHARGE`. eMSPs should accept these two new capabilities when they are provided by Gireve.
- All connector standards, including US types, are supported by Gireve and communicated to eMSPs.
- The fields "Publish_allowed_to", "Opening_times.exceptional_openings", "Charging_when_closed", "Images" and "Energy_mix" are not implemented by Gireve, therefore, the eMSP will not receive it.
- Gireve forwards the dynamic status changes of the EVSE using the CPO IDs of the location and EVSE.

4.4 Tokens module specifications

IOP follows the OCPI standard for Tokens module. [See OCPI 2.2.1 specifications.](#)

4.4.1 Push Tokens To IOP

CPOs connected to Gireve via OCPI 2.1.1 are required to have eMSPs, regardless of their protocol, transfer their full list of Tokens to Gireve.

PATCH Token to IOP is not yet implemented.

4.4.2 PULL Tokens From IOP

Pull Tokens From IOP is not implemented yet by IOP.

Tokens must be sent for roaming to work with OCPI 2.1.1 CPOs.

Information and Requirements

- eMSP tokens must be uploaded to the IOP to enable roaming with CPOs connected via OCPI 2.1.1.

4.5 Commands module specifications

IOP follows the OCPI standard for Commands received by a CPO. [See OCPI 2.2.1 specifications.](#)

4.5.1 "ocpi-to-country-code" and "ocpi-to-party-id" headers mandatory in StartSession and StopSession commands

eMSPs now receive locations with CPO IDs. Therefore, when an eMSP sends to IOP a start or stop session command, it is necessary to identify the CPO owner of the location by filling the 2 headers "ocpi-to-country-code" and "ocpi-to-party-id" by the CPO's `country_code` and `party_id`.

4.5.2 “evse_uid” mandatory in StartSession command

In OCPI 2.2.1 standard, the “evse_uid” property is optional for StartSession command. IOP requires it to do the mapping with the eMIP protocol.

4.5.3 “connector_id” optional in StartSession command

The connector_id field is optional in OCPI 2.2.1. If provided, it will be transmitted to the CPO in the start command.

4.5.4 ReserveNow command

The ReserveNow command is not implemented by IOP.

4.5.5 CancelReservation command

The CancelReservation command is not implemented by IOP.

4.5.6 UnlockConnector command

The UnlockConnector is not implemented by IOP.

Information and Requirements

- The “evse_uid” property is optional for the StartSession command, in OCPI 2.2.1 standard. However, IOP requires it for mapping with the eMIP protocol.
- In OCPI 2.2.1, the “connector_id” property is optional. If specified, it will be forwarded to the CPO in the start command.

4.6 Sessions module specifications

IOP follows the OCPI standard for Sessions sent by a CPO. [See OCPI 2.2.1 specifications.](#)

4.6.1 Session: Object IDs

The location_id, EVSE_uid, and connector_id fields within the session object are mapped to the IDs provided by the CPO platform. The uniqueness of these IDs is guaranteed by the combination of the country_code and party_id of the CPO in the body of the request.

The id field of the session object corresponds to the ID generated by Gireve and not the ID from the CPO platform.

4.6.2 Session: ‘VAT’

By default, Gireve will transmit the total_cost as provided by the CPO, including both excl_vat and incl_vat.

4.6.3 Session: 'SmartCharging'

The "Charging Preferences" object is not implemented by IOP. therefore, eMSPs cannot send "Charging Preferences" on behalf of the driver.

4.6.4 PULL Sessions ToIOP: Get List Pagination

Pull Session ToIOP is not currently implemented.

Information and Requirements

- Unlike Locations and Tariffs where IOP forwards CPO Ids to eMSPs, Session Ids and authorization references are replaced by Gireve ones. This decision has been made to ensure the consistency with other protocols and Gireve systems.
- Gireve billing feature doesn't consider or calculate VAT. In case costs are calculated by Gireve and included in Sessions/CDRs, VAT information is not filled.
- The "Charging Preferences" object is not implemented by IOP. therefore, eMSPs cannot send "Charging Preferences" on behalf of the driver.

4.7 CDRs module specifications

IOP follows the OCPI standard for CDRs sent by a CPO. [See OCPI 2.2.1 specifications.](#)

4.7.1 CDR: Object IDs

The id field of the CDR object is mapped with the id provided by the CPO platform.

The location_id, EVSE_uid, and connector_id fields within the CDR object are mapped to the IDs provided by the CPO platform.

The uniqueness of these IDs is guaranteed by the combination of the country_code and party_id of the CPO in the body of the request.

The session_id field of the CDR object corresponds to the ID generated by Gireve and not the ID from the CPO platform as done in the session module. [See Session: Object IDs](#)

4.7.2 CDR content

The "total_time" value is the total duration of this session (including the duration of charging and not charging).

It might not include the duration during which the EVSE is out of order so cannot supply the service. The out of order duration should be free of charge for eMSPs.

4.7.3 Add billing information in "Remark" field

In some cases, the CPO is not able to send a consistent B2B price in the CDR. ("total_cost" not mandatory for CPOs connected through eMIP protocol, CPO not able to calculate the price, ...)

For these reasons GIREVE has implemented a billing feature, included in its "Clearing" service, which calculates the B2B price for a given CDR and injects this information in the CDR.

IOP uses the "Remark" field in CDRs sent to the eMSP to send extra information about this billing.

The "Remark" field is prefixed by:

- [*] prefix: The total_cost provided in the CDR is calculated by Gireve.
- [?] prefix: The total_cost provided in the CDR is not significant. The B2B price has not been sent by the CPO and/or the eMSP has not subscribed to Gireve Clearing service.
- No prefix: The total_cost provided in the CDR has been sent by the CPO.

4.7.4 Fields Not Implemented by Gireve

CreditCDR

For the moment, the "credit" field is not implemented by Gireve; therefore, eMSPs will not receive it.

We recommend that the CPO transmit PATCH Sessions that Gireve will not consider at first, but that Gireve will consider at some point.

- CPO send CDR: Gireve records and sends to eMSP.
- CPO send CreditCDR: Gireve don't take in consideration.
- CPO send new CDR: Gireve records and sends to eMSP.

Credit_reference_id

The "credit_reference_id" field is not implemented by Gireve; therefore, eMSPs will not receive it.

Home_charging_compensation

The "home_charging_compensation" field is not implemented by Gireve; therefore, eMSPs will not receive it.

4.7.5 PULL CDRs ToIOP: Get List Pagination

Pull CDRs ToIOP is not currently implemented.

Information and Requirements

- Unlike Session IDs and authorization references, which are replaced with Gireve IDs, IOP forwards CDRs with CPO IDs to eMSPs. The same applies to Locations and Tariffs.
- IOP uses the "Remark" field in CDRs sent to the eMSP to send extra information about this billing.
- The fields "credit", "credit_reference_id" and "home_charging_compensation" are not implemented by Gireve, therefore, the eMSP will not receive it.

4.8 Tariffs module specifications

IOP follows the OCPI standard for Tariffs download by an eMSP. [See OCPI 2.2.1 specifications](#)

4.8.1 PULL Tariffs ToIOP: Object ID

The id field of the Tariff object is mapped with the id provided by the CPO platform.

4.8.2 PULL Tariffs ToIOP: “gireve_id” An Extra Gireve Property

Gireve will introduce a new field (not part of the OCPI protocol) called gireve_id. This is a unique ID generated by Gireve for each tariff.

4.8.3 PULL Tariffs ToIOP: Tariff Type

Gireve stores all tariffs coming from CPOs, whatever their nature, but transfers only “B2B Regular” tariffs to eMSPs.

4.8.4 PULL Tariffs ToIOP: CPO Targeting

If an eMSP wants to retrieve **all the tariffs of the CPOs** with which it has a roaming contract, it must use the IOP's **country_code** and **party_id** in the headers **ocpi_to_country_code** and **ocpi_to_party_id**.

If the eMSP wants to retrieve the tariffs of **a specific CPO** with which it has a roaming contract, it must use the CPO's **country_code** and **party_id** in the headers **ocpi_to_country_code** and **ocpi_to_party_id**.

4.8.5 PULL Tariffs ToIOP: eMSP Targeting

Gireve has introduced the ability for a CPO to target a specific eMSP when sending a tariff by adding two fields:

- target_operator_country_code
- target_operator_party_id

see [Differentiate tariff per eMSP](#)

Hence, eMSPs connected via OCPI 2.2.1 will receive, when pulling tariffs, the descriptions of the full list of valid tariffs from CPO(s), whether or not these tariffs are specific to the requesting eMSP.

Tariffs specific to an **eMSP** will have the fields **target_operator_country_code** and **target_operator_party_id** filled in.

4.8.6 PULL Tariffs ToIOP: Get List Pagination

If the eMSP wants to retrieve a list of tariffs, it can call the URL: /ocpi/sender/2.2.1/tariff?date_from= using the paginated properties date_from, date_to, offset and limit.

Parameters « offset » and « limit » are optional but IOP always returns a paginated response (subset of objects list and link, X-Total-Count and X-limit headers).

The eMSP must call **the link returned in the headers** to get the next pages.

IOP has its own max limit (**100 Tariffs**) and answers with its if the client limit is upper than IOP one or the client doesn't set its limit.

The timeframe ('date_from' and 'date_to') used in the request parameters must be lower than **one month**.

4.8.7 Specific properties added by Gireve


TariffDimensionType "SESSION_TIME"

In standard OCPI V2.2.1, the CPO can define 2 different "TariffDimensionType" related to the duration:

- **TIME:** "time charging: defined in hours, step_size multiplier: 1 second" *(description from the OCPI Github)*.
- **PARKING_TIME:** "time not charging: defined in hours, step_size multiplier: 1 second" *(description from the OCPI Github)*.

Gireve adds a third "TariffDimensionType" named "SESSION_TIME" with the following description:

- **SESSION_TIME:** "time charging or not: defined in hours, step_size multiplier: 1 second".



Information and Requirements

- The "id" field of the tariff object is mapped to the identifier provided by the CPO.
- Gireve include a new field, gireve_id, which is not part of the OCPI protocol. This field will be a unique identifier generated by Gireve for each tariff.
- Gireve stores all tariffs coming from CPOs, whatever their nature, but transfers only "B2B Regular" tariffs to eMSPs.
- By filling the 2 headers "ocpi-to-country-code" and "ocpi-to-party-id" by the CPO's country_code and party_id, the eMSP is able to retrieve only the tariffs of this specific CPO.
- Tariffs specific to an eMSP will have the fields "target_operator_country_code" and "target_operator_party_id" filled in.
- eMSPs can now receive a new TariffDimensionType called SESSION_TIME (charging time + parking time).